MÜTHING FRONT CHOPPER MULTI CHOPPER MZO 200







CONVICING ADVANTAGES:

- PRECISELY CHOPPED CROPS
- MASSIVE ABSORBENCY
- THE DUST STAYS ON THE FIELD
- VERSATILE USAGE
- ADJUSTABLE CHOPPING LENGTH



Müthing GmbH & Co. KG Soest Am Silberg 23

D-59494 Soest

Tel. +49 (0) 2921 96510 Fax + 49 (0) 2921 73080

soest@muething.com www.muething.com MÜTHING FRONT CHOPPER MULTI CHOPPER MZO 200

FOR NEW HOLLAND SQUARE BALERS

MÜTHING FRONT CHOPPER **MULTI CHOPPER MZO 200**

PERFECTLY MATCHED TO YOUR **NEW HOLLAND SQUARE BALER**

Convincing advantages:

PRECISELY CHOPPED CROPS

Not just short, but shredded.

MASSIVE ABSORBENCY

Chopped baled straw has approx. 20 % greater absorbency compared to long baled straw*.

THE DUST STAYS ON THE FIELD

The ventilation generated by the chopping process releases fine dust and crude ash from the crop.

VERSATILE USAGE

As bedding in cowshed, poultry or other feeding stalls and as a raw fibre supplement in mixed feed rations. Approx. 10% less crude ash content in chopped straw bales compared to conventionally baled straw*.

ADJUSTABLE CHOPPING LENGTH

Two adjustable shear bars for adjusting the chopping length. All knives of the rotor and shear bar are usable on both sides.







Optimally shredded crops for maximum absorbency.

Firm and stable square bales thanks to precisely chopped crops.

TOP-CLASS INTERACTION



- Müthing MZO front chopper with high-speed rotor shaft for uniform swath pick-up, chopping and delivery of the choppings
- Perfectly matched to New Holland square balers





- Rotor with 88 extra-long rotor knives made of special wear-resistant steel, serrated and usable on both sides - for fin chopping of the crop.
- Two adjustable shear bars, each with 45 serrated knives for different chopping lengths









- Screw-on intermediate mounting bracket for drawbar (baler-specific)
- · Chopper height adjustment with two side pull cylinders and synchronising valve





- Chopper drive with special driveshaft from intermediate gear box to side belt drive, with spring-assisted, automatic clamping device
- Strong intermediate gear box, designed for tractors over 220 kW, with integrated freewheel and engagement/disengagement of chopper drive



- Adjustable rear ejector plate with guide plates to bring the choppings together for feed into the baler intake duct
- Adjustable chopper depth limiter





- Transport wheels for mounting and dismounting on the square baler
- Easy manoeuvring of chopper attachment for fast deployment

Optional equipment:

- PTO shaft with wide angle between tractor and transfer gearbox as standard, for powering the chopper and the baler
- Hydraulic support foot, for baler with shutoff valve
- Guide wheels
- Mounting and assembly of MZO 2011 chopper attachment (please enquire for mounting options, mounting locations, prices and delivery times)

Technical specifications:

reclinical specifications.	
MULTI CHOPPER MZO 200	2000
Working width (cm)	200
Number of knives	88
Knife rotation speed (m/sec)	Approx. 92
Weight (kg) without detachable parts, intermediate bracket and gear box	900

^{*}Findings of a 2016 Bachelor's dissertation at the University of Weihenstephan Triesdorf: Different forms of preparing straw using the rotary cutter of a square baler and engageable front chopper